



Lyden Oil Company

ProGuard

Product Information

***ProGuard* RP 3WD**

***ProGuard* RP 3WD** is an all-purpose penetrating oil and rust preventive that is exceptionally stable in wet conditions. It provides rapid displacement and separation of water and leaves an excellent thin film protection.

***ProGuard* RP 3WD** is designed for use where there is alkaline, acid or solvent emulsion rinse water left on parts. ***ProGuard* RP 3WD** resists these types of contamination very well.

Typical Properties

***ProGuard* RP 3WD**

Recommended Film Thickness	0.10 mils
Film Type	Transparent, Oily
Theoretical Coverage	1900 sq. ft./gallon
Water Displacement, (MIL-C-16173D)	PASS
Flash Point, °C (°F), ASTM D-92	40.5° (105°)
Humidity Cabinet, 120 °F, ASTM D-1748	30 day min.
Indoor Storage	Up to one year
Viscosity, cSt at 40 °C, ASTM D-445	2.5

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com