Lyden Oil Company
ProGuard Product Data

ProGuard Premium Lithium EP Greases
Product Data Sheet

ProGuard Premium Lithium EP Greases are lithium thickened, multi-functional extreme pressure (EP) greases formulated to withstand constant temperatures up to 250 Deg. F for extended periods of time, protect against wear, rust and resistant to water washout.

ProGuard Premium Lithium EP Greases are designed for both on and off-highway equipment, construction equipment and industrial uses. Applications include and are not limited to ball and roller bearings, antifriction and plain bearings, bushings, cams, splines, universal joints, pins, slides, motor bearings, centralized lubrication systems (EP 0 & 1), and other applications that require a premium extreme pressure grease.

Benefits

- High melting point
- High load carrying ability to reduce wear under heavy or shock loading and vibration
- Extreme pressure protection
- Protects against rust and corrosion where moist or wet environments are common
- Excellent resistance to water washout
- Stays in place to extend component life
- Wide operating ranges (-4 to 250 Deg F)

Typical Characteristics

ProGuard Premium Lithium Greases	**0**	**1**	**2**
Color	Med Amber	Med Amber	Med Amber
Appearance	Smooth	Smooth	Smooth
Thickener	Lithium	Lithium	Lithium
Base Oil Viscosity ASTM D445 @40 Deg. C, cSt	180	180	180
Dropping Point, Deg F. ASTM 2265	365	365	365
Deg. C	185	185	185
Timken OK Load, lbs ASTM D2509	40	40	40
Four Ball EP Weld, kg ASTM D2596	315	315	315
Rust Protection, ASTM D6138	Pass	Pass	Pass

100430

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342