



# **Lyden Oil Company**

## **ProGuard Product Data**

### **ProGuard Spindle Oil's Product Data Sheet**

**ProGuard Spindle Oil's** are premium quality, highly refined lubricants formulated for use in high speed, lightly loaded bearings.

**ProGuard Spindle Oil's** contain a carefully balanced additive package that provides excellent oxidation stability, rust protection and resistance to deposit formation.

**ProGuard Spindle Oil's** have excellent water separation characteristics and anti-wear properties and can be used in machine tools that have run speeds of 20,000 – 40,000 rpm.

#### **Benefits**

- Excellent oxidation stability
- Excellent anti-wear protection
- Rust and oxidation protection
- Outstanding water separation characteristics
- Low viscosity products to aid in heat reduction

#### **Typical Characteristics**

<b>ProGuard Spindle Oil</b>	<b>2</b>	<b>10</b>	<b>22</b>
Viscosity, 40 Deg C	2	10	20.6
Flash Point, Deg F	170	335	365
Pour Point, Deg F	-27	-27	-22
Rust Test	PASS	PASS	PASS

110111

### **Lyden Oil Company**

3249 Wales Ave. NW  
Massillon, OH 44646  
(330)832-7800  
fax: (330)832-2787

3711 LeHarps Rd.  
Youngstown, OH  
(800)362-9410  
fax: (330)792-1462

2649 Tracy Rd.  
Northwood, OH  
(800)245-9336  
fax: (419)666-8790

419 Spring St.  
Lansing, MI 48101  
(800)968-6457  
fax: (517)485-0605

24200 W. Outer Dr.  
Allen Park, MI 48912  
(313)383-0097  
fax: (313)383-2342