



Lyden Oil Company

ProGuard

Product Information

ProGuard 142 HT Solvent

ProGuard 142 HT Solvent is a refined blend of light, hydrotreated isoparaffin and naphthenic distillates with very low levels of polynuclear aromatics. It is a clear liquid with a medium flash point and mild odor.

Applications

- General Cleaning and Degreasing
- Parts Washing
- Chemical Process Solvent
- Oilfield Drilling Fluid
- Metal Rolling Oil
- Lamp Oil

Typical Properties

ProGuard 142 HT Solvent

Product Code Number	911021
Viscosity, ASTM D-445 cSt at 40 °C	1.3
Flash Point, °C (°F), ASTM D-56	>61 (>142)
Pour Point, °C (°F), ASTM D-97	<-70 (<-94)
Aniline Point, °C (°F), ASTM D-611	68 (154)
Specific Gravity at 60 °F, ASTM D-287	0.802
Density, lbs/gal at 60 °F, ASTM D-287	6.71
Average Molecular Weight, API Method	156
Relative Evaporative Rate (n-Butyl Acetate = 1)	0.1

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com