



Lyden Oil Company

ProGuard

Product Information

ProGuard Rock Drill 150E

ProGuard Rock Drill 150E is specially designed for lubrication of all makes of pneumatic percussion tools - rock drills, jack-hammers, tampers, riveters, chippers and pavement breakers.

ProGuard Rock Drill 150E is boosted with several times the normal ashless dispersancy additive, and formulated with extreme pressure and rust-prevention properties. In addition, it has a high degree of emulsibility plus tackiness agents to prevent water from wetting metal surfaces or displacing the lubricant.

Typical Properties

ProGuard

Rock Drill Oil

150E

Product Code Number	17869
Viscosity, ASTM D-445	
cSt at 100 °C	14.5
cSt at 40 °C	142
Viscosity Index	100
Flash Point, °C (°F), ASTM D-92	263 (505)
Pour Point, °C (°F), ASTM D-97	-21 (-5)
API Gravity, ASTM D-287	31.6
Demulsibility, ASTM D-1401	
Min. to Separate	40
Timken OK Load, lbs., ASTM D-2782	70
Consistency	Stringy

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com