



Lyden Oil Company

ProGuard

Product Information

ProGuard AW 22 MG Blue Hydraulic Oil

ProGuard AW 22 MG Blue Hydraulic Oil is a premium quality, multigrade hydraulic fluid designed to lubricate and protect mobile hydraulic systems. It has excellent high and low temperature viscometrics as well as outstanding shear stability. In addition, it is formulated for anti-wear protection, rust protection, anti-foam protection and excellent water separation properties.

ProGuard AW 22 MG Blue Hydraulic Oil is designed to satisfy the operating needs of most types of mobile and stationary hydraulic equipment exposed to low and abnormally low temperatures. It will reduce lengthy warm-up and sluggish operation, and is formulated with the highest quality, shear stable viscosity improver to assure long term lubricant performance by minimizing permanent viscosity loss.

Suitable Applications

FMC 40 P0014-C, 40 P0013-C, 830552

Lee-Norse 100-1

Jeffrey No. 87

U.S. Steel 127, 136

B.F. Goodrich 0152

GM LH-04-1, LH-06-1, LH-15-1

Racine Model S, variable volume vane pump

Cincinnati Milacron P-68, P-69, P-70

DIN 51524, Part 2

Poclair multigrade specification

Swedish SHS multigrade

Sperry Vickers I-286-S, M-2950-S

Denison HF-1, HF-2, HF-0

Typical Properties

ProGuard

AW 22 MG Blue Hydraulic Oil

Product Code Number	17974
Viscosity, ASTM D-445	
cSt at 100 °C	4.6
cSt at 40 °C	22.0
Viscosity Index	130
Flash Point, °C (°F), ASTM D-92	181 (358)
Pour Point, °C (°F), ASTM D-97	-40 (-40)
Demulsibility, 130 °F, ASTM D-1401	Pass

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com