



Lyden Oil Company

ProGuard

Product Information

ProGuard Mist Lubes

ProGuard Mist Lubes are premium, heavy duty, anti-wear hydraulic oils developed to meet the requirements of machines lubricated by oil-fog or oil-mist methods. They provide excellent wear protection against heavy loads and have good surface wetting characteristics.

ProGuard Mist Lubes are characterized by good EP protection, excellent oxidation resistance and exceptional anti-foaming properties. They are a good choice for mist lubrication for bearings, gears, screws, and metallic ways.

Typical Properties

ProGuard Mist Lubes

	32	46	68	100	220
Product Code Number	17813			17994	
Viscosity, ASTM D-445					
cSt at 100 °C	5.5	6.7	8.1	11.0	18.1
cSt at 40 °C	33.3	46.2	62.5	96.3	209
Viscosity, ASTM D-2161					
SUS at 210 °F	44	48	54	64	93
SUS at 100 °F	160	230	330	500	1100
Viscosity Index	100	98	96	99	95
API Gravity	31.2	30.3	29.5	27.8	28.9
Flash Point, °C (°F), ASTM D-92	215 (420)	221 (430)	232 (450)	260 (500)	276 (530)
Pour Point, °C (°F), ASTM D-5950	-29 (-20)	-29 (-20)	-29 (-20)	-23 (-10)	-17 (0)
Oxidation Stability, Hrs, ASTM D-943	2000+	2000+	2000+	2000+	2000+
Rust Test, ASTM D-665	Pass	Pass	Pass	Pass	Pass

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com