



Lyden Oil Company

ProGuard

Product Information

ProGuard ProCut 190SCF

ProGuard ProCut 190SCF is a general purpose cutting oil for use with carbon steels and alloy steels.

ProGuard ProCut 190SCF contains active sulfur, a non-chlorine EP additive, and an anti-misting agent.

Applications:

- Threading
- Drilling
- Tapping
- Grinding
- Milling
- Broaching
- Turning

Typical Physical Characteristics:

ProGuard ProCut 190SCF

Product Code Number	17856
Viscosity, ASTM D-88 SUS at 100° F	200
Flash Point, ASTM D-92, °F (°C)	350 (176)
Sulfur, %	1.1
Active Sulfur, %	1.0
Fat, %	0.0
Chlorine, %	0.0
Anti-Mist	Yes

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465

1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Drive
Youngstown, OH 44515

1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906

1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317

local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646

local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com