



# **Lyden Oil Company**

## **ProGuard Product Data**

### **ProGuard Line Wash** **Product Data Sheet**

**ProGuard Line Wash** is a blend of similar products that are blended together for use in applications where low hour, low pressure and economics are of concern. Other applications include light duty hydraulics, flushing oil, sealing/barrier applications, light duty gear boxes and applications where a light duty oil film is needed to prevent metal to metal contact from occurring.

#### **Benefits**

- Provides Fluid Film Protection
- Prevents Metal to Metal Contact from Occurring
- Separates from Water
- Inhibits Rust and Corrosion
- Controls Oxidation
- Compatible with Common Filter Media

#### **Typical Properties**

ProGuard Line Wash

ISO Grade	46/68/100
Viscosity	
@40 Deg C, Cst	46 – 80
@ 100 Deg C, Cst	6.7 – 9.7
Pour Point, Deg F	-20

080414

### **Lyden Oil Company**

3249 Wales Ave. NW  
Massillon, OH 44646  
(330)832-7800  
fax: (330)832-2787

3711 LeHarms Rd.  
Youngstown, OH  
(800)362-9410  
fax: (330)792-1462

2649 Tracy Rd.  
Northwood, OH  
(800)245-9336  
fax: (419)666-8790

419 Spring St.  
Lansing, MI 48101  
(800)968-6457  
fax: (517)485-0605

24200 W. Outer Dr.  
Allen Park, MI 48912  
(313)383-0097  
fax: (313)383-2342