



Lyden Oil Company

ProGuard Product Data

ProGuard Spargrind Oil 60 **Low Viscosity Cutting & Grinding Fluid** **Product Data Sheet**

ProGuard Spargrind Oil 60 is a low viscosity, high flash point, straight oil designed for use in high surface quality applications. The specialized anti-mist additive incorporated into **ProGuard Spargrind Oil 60** make the product an ideal choice for high speed grinding applications. Extreme pressure additives coupled with the product's low viscosity assure excellent cooling and wetting properties. **ProGuard Spargrind Oil 60** provides the machine operator high visibility of the work piece due to the clarity of the product. The select base stocks used in formulating **ProGuard Spargrind Oil 60** feature very good oxidation stability for long term use in grinding applications.

Outstanding Features

- Low Viscosity for Excellent Cooling and Chip Settling
- Clean Formula for High Visibility
- Good Oxidation Stability
- Exclusive Anti Mist Additive
- Outstanding Surface Finish

Typical Applications Include

- Grinding
- Cutting
- Drilling

Physical Specifications

Color	Yellow
Odor	Characteristic
Appearance	Clear, Liquid
Viscosity @ 40°C Cst	9.0-13.0
Viscosity @ 100°F Sus	55-70
Specific Gravity @ 60°F	0.8502
Flash Point	375°F
Density (lbs/gal)	7.080

071116

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342