



Lyden Oil Company

ProGuard Product Data

ProGuard Sparkut SC **Cutting, Stamping, Drawing & Blanking** **Product Data Sheet**

ProGuard Sparkut SC is a medium to heavy duty straight oil designed for all ferrous type metal working applications. It is highly additized with extreme pressure components and contains a specialized vegetable oil ester anti mist formula. The advanced chemical technology built into **ProGuard Sparkut SC** makes this an ideal choice for reducing airborne fog and mist in high speed operations. The combination of active sulfur and chlorine will provide excellent anti weld boundary lubrication between tool and work piece. **ProGuard Sparkut SC** is a highly additized straight oil designed for medium to heavy duty machining operations. It can be used in stamping and drawing operations where reduced levels of airborne mist are of benefit to user and the environment.

Outstanding Features

- Multipurpose Straight Oil
- Low Mist/Anti Fog Additives
- Excellent Anti-Weld Characteristics
- Transparency Provides Good Visibility

Typical Applications Include

- Cutting
- Stamping
- Drawing
- Blanking
- Milling
- Gear Hobbing

Physical Specifications

Color	Yellow
Odor	Characteristic
Appearance	Clear, Liquid
Viscosity @ 40°C Cst	32.0-40.0
Viscosity @ 100°F Sus	150-185
A.P.I. Gravity @ 60°F	28.6
Specific Gravity @ 60°C	0.8839
Density (lbs/gal)	7.360

071116

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarps Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342