



Lyden Oil Company

ProGuard Product Data

ProGuard VSL-85 Vanishing Oil **Product Data Sheet**

ProGuard VSL-85 Vanishing Oil is an evaporative forming lubricant that has been used in the stamping, forming and drawing manufacturing process. It may be used on copper, steel and aluminum. **ProGuard VSL-85 Vanishing Oil** is particularly designed for fin stamping and end sheet production in shops which do not clean their coils. It is compatible with most painting and brazing operations as well as being compatible with most refrigerants.

It is non-gumming to keep machines clean and free of sticky residue.

ProGuard VSL-85 Vanishing Oil leaves a fine layer of corrosion protective on the parts.

Typical Characteristics:

Color	Pale Yellow
Odor	Typical
Appearance	Clear, liquid
Viscosity	
Cst @ 40 Deg. C	2.45
SUS @ 40 Deg. C	34
Specific Gravity @60 Deg F.	0.7660
Density, lb/gal	6.38
Flash Point, Deg. F	142

080715

Lyden Oil Company

3249 Wales Ave. NW
Massillon, OH 44646
(330)832-7800
fax: (330)832-2787

3711 LeHarms Rd.
Youngstown, OH
(800)362-9410
fax: (330)792-1462

2649 Tracy Rd.
Northwood, OH
(800)245-9336
fax: (419)666-8790

419 Spring St.
Lansing, MI 48101
(800)968-6457
fax: (517)485-0605

24200 W. Outer Dr.
Allen Park, MI 48912
(313)383-0097
fax: (313)383-2342