



Safety Data Sheet

Lyden Oil Company

Page 1 of 8

PROGUARD Poly-Moly Grease

SDS Number: 60155

1 PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Poly-Moly Grease
Revision Date: 08/06/2015
SDS Number: 60155
Common Name: PROGUARD Poly-Moly Grease
CAS Number: Blend
Product Code: 1005
Synonyms: Poly-Moly Grease

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word: **None**

Hazard Classes/Categories: None

Hazard Statement(s): None

Precaution Statement(s):
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.

PROGUARD Poly-Moly Grease

SDS Number: 60155

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 1

Reactivity = 0

3 COMPOSITION / INFORMATION ON INGREDIENTSIngredients:*Mixture of the substances listed below with nonhazardous additions.*

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	25-50
Molybdenum Disulphide	1317-33-5	1-2.5
Zinc Dialkylthiophosphate	68457-79-4	0.1-<1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.*4** FIRST AID MEASURESDescription of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact:

Generally the product does not irritate the skin.

Eye Contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.

Ingestion:

If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment.

PROGUARD Poly-Moly Grease

SDS Number: 60155

Symptoms and Effects, both acute and delayed:

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable for the environment.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin and eyes.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

PROGUARD Poly-Moly Grease

SDS Number: 60155

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Do not allow to enter ground waters.

Cleanup Procedures:

Absorb with liquid-binding material (sand, diatomite, acid binders, iniversal binders, sawdust.

7 **HANDLING AND STORAGE**Handling Precautions:

No special precautions needed if used correctly.

Storage Requirements:

Keep container tightly sealed.

8 **EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (25-50%):

ACGIH TLV – Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (2.5-<10%):

ACGIH TLV – Short-term value: 10mg/m³

Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-64742-01-4 Residual oils (petroleum), solvent-refined (25-50%):

OSHA PEL – Long-term value: 5mg/m³

-26221-73-8 1-Octene, polymer with ethane (2.5-<10%):

NUISANCE DUST TLV – Long-term value: 10

PROGUARD Poly-Moly Grease

SDS Number: 60155

-1317-33-5 Molybdenum disulphide (1-2.5%):

PEL - Long-term value: 15mg/m³ (total dust)

TLV - Long-term value: 10mg/m³ (inhalable fraction), 3mg/m³(respirable fraction)

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.
Use safety glasses and gloves.

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Color:	Grey
Physical State:	Semi-solid
Odor:	Petroleum-like
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	338° C / 640° F
Boiling Range:	Data not available
Flash Point:	255° C / 491° F
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.837 pounds per gallon at 68° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

PROGUARD Poly-Moly Grease

SDS Number: 60155

10 STABILITY AND REACTIVITYStability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not expected to form.

11 TOXICOLOGICAL INFORMATIONRoutes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

No known irritating or sensitizing effects.

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 4427 mg/kg (rat)

Dermal LD50: 169492 mg/kg (rabbit)

Inhalative LC50: 1100 mg/l (4 hours)

PROGUARD Poly-Moly Grease

SDS Number: 60155

Carcinogenic/Mutagenic Precautions:

1-Octene, polymer with ethene: Carcinogenic category 3 (IARC).

12 ECOLOGICAL INFORMATIONEcological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONSDisposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:Small quantities can be disposed of with household garbage.
Do not flush to surface waters or drains.**14** TRANSPORT INFORMATION

<u>UN Number:</u>	Data not available
<u>UN Shipping Name:</u>	Data not available
<u>Transport Hazard Class:</u>	Data not available
<u>Packing Group:</u>	Data not available

Environmental Hazards:

Data not available



Safety Data Sheet

Lyden Oil Company

Page 8 of 8

PROGUARD Poly-Moly Grease

SDS Number: 60155

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 08/06/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.