



Safety Data Sheet

Lyden Oil Company

Page 1 of 8

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

1	PRODUCT AND COMPANY INFORMATION
----------	--

Product Name: PROGUARD A-Plex EP2 Grease
Revision Date: 11/25/2015
SDS Number: 60905-2
Common Name: PROGUARD A-Plex EP2
CAS Number: Blend
Product Code: 60905-2
Synonyms: A-Plex No. 2

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Signal Word: **None**

Hazard Classes/Categories: None

Hazard Statement(s): None

Precaution Statement(s):
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Other Hazard Statement(s):

-NFPA Ratings:

Health = 1

Fire = 1

Reactivity = 0

3 COMPOSITION / INFORMATION ON INGREDIENTSIngredients:*Mixture of the substances listed below with nonhazardous additions.*

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	50-100
Asphaltic Resin	8052-42-4	25-25
Alkenes, Polymerized, Chlorinated	68410-99-1	2.5-10
Antimony dialkyldithiocarbamate	15890-25-2	0.1-2.5
Antimony 0,0-dipropylphosphorodithioate	15874-48-3	0.1-2.5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.*4** FIRST AID MEASURESDescription of First Aid Measures:

Inhalation:

Remove person to fresh air and keep comfortable breathing. Call a POISON CENTER and consult medical attention if you feel unwell.

Skin Contact:

Wash with plenty of water, if skin irritation occurs: get medical attention. Remove contaminated clothing and wash before reuse.

Eye Contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable for the environment.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin and eyes.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter ground waters.

Cleanup Procedures:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 HANDLING AND STORAGE

Handling Precautions:

Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Do not cut, weld, drill, grind, braze, or solder container.
Keep away from sources of ignition.

Storage Requirements:

Keep container tightly closed and in a cool, well-ventilated area. Keep away from sources of ignition.
Store locked up.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (50-100%):

ACGIH TLV – Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-Asphaltic Resin (25-25%):

PEL - Long-term value: 5mg/m³

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

REL – Short-term value: 10mg/m³
 Long-term value: 5mg/m³
 Ceiling limit value: 5mg/m³ (15 minutes)
 TLV – Short-term value: 10mg/m³
 Long-term value: 5mg/m³
 BEI – Medium: urine, Time: end of shift at end of workweek, Parameter: 1-Hydroxyrene with hydrolysis (nonquantitative)

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Use safety glasses and gloves.

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Color:	Black
Physical State:	Semi-solid
Odor:	Petroleum-like
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	427° C / 801° F
Boiling Range:	Data not available
Flash Point:	255° C / 491° F
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.727 pounds per gallon
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Decomposition Temperature: Data not available
Viscosity: Data not available

10 STABILITY AND REACTIVITYStability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not expected to form.

11 TOXICOLOGICAL INFORMATIONRoutes of Exposure:

Skin, eye contact, and inhalation are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:Irritant to skin and mucous membranes.
Irritant to eyes.
Inhalation of vapors or mists may cause irritation.

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 12359 mg/kg

Dermal LD50: 8089 mg/kg (rabbit)

Inhalative LC50: 95.4 mg/l (4 hours) (rat)

Carcinogenic/Mutagenic Precautions:

Asphaltic resin: Carcinogenic category 2B (IARC).

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number: Data not available

UN Shipping Name: Data not available

Transport Hazard Class: Data not available

Packing Group: Data not available



Safety Data Sheet

Lyden Oil Company

Page 8 of 8

PROGUARD A-Plex EP2 Grease

SDS Number: 60905-2

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15	REGULATORY INFORMATION
-----------	-------------------------------

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION
-----------	--------------------------

Last Revision Date: 11/25/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.