

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

1 PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD CSG 100-1 Grease
Revision Date: 08/12/2015
SDS Number: 61182-1/100
Common Name: PROGUARD Calcium Sulfonate Complex 1 ISO 100 grease
CAS Number: Blend
Product Code: 1056
Synonyms: No. 1 EP Calcium Sulfonate Complex ISO 100

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Eye irritant, Category 2A.

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

Hazard Statement(s):

H319: Causes serious eye irritation.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P264: Wash hands thoroughly after handling.

P280: Wear protective eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P337+313: If eye irritation persists get medical advice/attention.

P405: Store locked up.

P501: Dispose of contents/container to in accordance with local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 1

Reactivity = 0

3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
C10-C16 alkylbenzenesulfonic acid calcium salt	68584-23-6	2.5-<10
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	25-50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10-<25
Calcium carbonate	471-34-1	2.5-<10

**Any concentration shown as a range is to protect confidentiality or is due to batch variation.*

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

4 FIRST AID MEASURESDescription of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact:

Generally the product does not irritate the skin.

Eye Contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURESRecommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable for the environment.

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin and eyes.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Do not allow to enter ground waters.

Cleanup Procedures:

Absorb with liquid-binding material (sand, diatomite, acid binders, iniversal binders, sawdust.

7 HANDLING AND STORAGE

Handling Precautions:

No special precautions needed if used correctly.

Storage Requirements:

Keep container tightly sealed.

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

8 EXPOSURE CONTROLS / PERSONAL PROTECTIONExposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (25-50%):

ACGIH TLV – Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (10-<25%):

ACGIH TLV – Short-term value: 10mg/m³

Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-471-34-1 Calcium carbonate, precipitated (2.5-<10%):

PEL - Long-term value: 15mg/m³ (total dust), 5mg/m³ (respirable fraction)

REL - Long-term value: 10mg/m³ (total dust), 5mg/m³ (respirable fraction)

TLV – TLV withdrawn

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.
Use safety glasses and gloves.

9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Light grey
Physical State:	Semi-solid
Odor:	Petroleum-like
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	370° C / 698° F
Boiling Range:	Data not available

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

Flash Point:	255° C / 491° F
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	10.080 pounds per gallon at 68° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

10 STABILITY AND REACTIVITYStability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not expected to form.

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

No known irritating or sensitizing effects.

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 38610 mg/kg (rat)

Dermal LD50: 100000 mg/kg (rabbit)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagenic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

Water hazard class 1 (self-assessment): Slightly hazardous to water.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

PROGUARD CSG 100-1 Grease

SDS Number: 61182-1/100

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number: Data not available
UN Shipping Name: Data not available
Transport Hazard Class: Data not available
Packing Group: Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATIONLast Revision Date: 08/12/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.