



Safety Data Sheet

Lyden Oil Company

Page 1 of 9

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

1 PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD NL1A Plus Gear Oil
Revision Date: 08/10/2015
SDS Number: 61079-460
Common Name: PROGUARD NL1A Plus
CAS Number: Blend
Product Code: 1016
Synonyms: ISO 460 Gear Oil

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word: **None**

Hazard Classes/Categories: None

Hazard Statement(s): None

Precaution Statement(s):
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

Other Hazard Statement(s):

-NFPA Ratings:
 Health = 1
 Fire = 1
 Reactivity = 0

3	COMPOSITION / INFORMATION ON INGREDIENTS
----------	---

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	50-100
Asphaltic Resin	8052-42-4	25-50
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1-2.5
Antimony dialkyldithiocarbamate	15890-25-2	1-<2.5
Antimony dialkyldithiocarbamate	15890-25-2	0.1-<1
Antimony 0,0-dipropylphosphorodithioate	15874-48-3	0.1-<1

**Any concentration shown as a range is to protect confidentiality or is due to batch variation.*

4	FIRST AID MEASURES
----------	---------------------------

Description of First Aid Measures:

Inhalation:

Remove person to fresh air and keep comfortable breathing. In case of unconsciousness, place patient stably in side position for transportation. Call a POISON CENTER and consult medical attention if you feel unwell.

Skin Contact:

Wash with plenty of water, if skin irritation occurs: get medical attention. Remove contaminated clothing and wash before reuse.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

Eye Contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable for the environment.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin and eyes.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter ground waters.

Cleanup Procedures:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7	HANDLING AND STORAGE
----------	-----------------------------

Handling Precautions:

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Storage Requirements:

Keep container tightly closed and in a cool, well-ventilated area. Keep away from sources of ignition. Store locked up. Keep container tightly sealed.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

8 EXPOSURE CONTROLS / PERSONAL PROTECTIONExposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (50-100%):

ACGIH TLV – Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-Asphaltic Resin (25-50%):

PEL - Long-term value: 5mg/m³

REL – Short-term value: 10mg/m³

Long-term value: 5mg/m³

Ceiling limit value: 5mg/m³ (15 minutes)

TLV – Short-term value: 10mg/m³

Long-term value: 5mg/m³

BEI – Medium: urine, Time: end of shift at end or workweek, Parameter: 1-

Hydroxyrene with hydrolysis (nonquantitative)

-64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (1-2.5%):

ACGIH TLV – Short-term value: 10mg/m³

Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

-15890-25-2 Antimony dialkyldithiocarbamate (1-2.5%):

ACGIH TLV – Long-term value: 0.5mg/m³

NIOSH REL - Long-term value: 0.5mg/m³

OSHA PEL – Long-term value: 0.5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. Use safety glasses and gloves.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Dark brown
Physical State:	Liquid
Odor:	Petroleum-like
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	427° C / 801° F
Boiling Range:	Data not available
Flash Point:	255° C / 491° F
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.587 pounds per gallon at 68° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

10 STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
<u>Reactivity:</u>	Not reactive under normal conditions.
<u>Conditions to Avoid:</u>	No further relevant information available.
<u>Hazardous Reactions:</u>	No known hazardous reactions.
<u>Incompatible Materials:</u>	No further relevant information available.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

Decomposition Products:

Hazardous decomposition products are not expected to form.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin, eye contact, and inhalation are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

Irritant to skin and mucous membranes.
Irritant to eyes.
Inhalation of vapors or mists may cause irritation.

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 5359 mg/kg
Dermal LD50: 5109 mg/kg (rabbit)
Inhalative LC50: 367 mg/l (4 hours)

15890-25-2 Antimony dialkyldithiocarbamate:

Oral LD50: 16400 mg/kg (rat)
Dermal LD50: 16000 mg/kg (rabbit)
Inhalative LC50: 11 mg/l (4 hours) (ATE)

Carcinogenic/Mutagenic Precautions:

Asphaltic resin: Carcinogenic category 2B (IARC).

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

Ecological Effects:

-15890-25-2 Antimony dialkyldithiocarbamate:

EC50: 0.063 mg/kg (daphnia)

-Water hazard class 1 (self-assessment): Slightly hazardous to water.

13 DISPOSAL CONSIDERATIONSDisposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:Do not dispose of with household garbage.
Do not flush to surface waters or drains.**14** TRANSPORT INFORMATIONUN Number: Data not availableUN Shipping Name: Data not availableTransport Hazard Class: Data not availablePacking Group: Data not availableEnvironmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.



Safety Data Sheet

Lyden Oil Company

Page 9 of 9

PROGUARD NL1A Plus Gear Oil

SDS Number: 61079-460

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 08/10/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.