

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

1 PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Merit Honing Oil 20 EP
Revision Date: 12/17/2015
SDS Number: 17936
Common Name: Hydrotreated middle petroleum oil
CAS Number: Blend
Product Code: 17936
Synonyms: Petroleum based lubricant

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515

For Product Information: 1-330-792-1100
For Emergencies: 1-800-424-9300
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATIONSignal Word:**DANGER**Hazard Classes/Categories:

Aspiration hazard, Category 1.
Skin irritant, Category 2.
Serious eye irritation, Category 2B.

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H320: Causes eye irritation.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand.
 P102: Keep out of reach of children.
 P103: Read label before use.
 P302+352: IF ON SKIN: Wash with plenty of water.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
 P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor
 P331: Do NOT induce vomiting.
 P405: Store locked up.
 P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3	COMPOSITION / INFORMATION ON INGREDIENTS
----------	---

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Hydrotreated middle petroleum	64742-46-7	70-80
Fats and glyceridic oils, sulfurized	68990-81-8	15-25
Non-hazardous additives	Proprietary	<10

**Any concentration shown as a range is to protect confidentiality or is due to batch variation.*

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

4 FIRST AID MEASURESDescription of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

Eye Contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURESRecommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing.
Keep away from sources of ignition.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water course.
Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.

7 HANDLING AND STORAGE

Handling Precautions:

Handle with care and avoid spillage on the floor.
Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed.
Keep away from sources of ignition.

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

8 EXPOSURE CONTROLS / PERSONAL PROTECTIONExposure Limits:

No data available.

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:Wash hands before breaks and at the end of work.
Use safety glasses and gloves.**9 PHYSICAL AND CHEMICAL PROPERTIES**

Color:	Dark Amber
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	135° C / 275° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.3 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	8 mm ² /sec (kinematic at 40° C)

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not expected to form.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an oil acne.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagenic.

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number: Data not available

UN Shipping Name: Data not available

Transport Hazard Class: Data not available

Packing Group: Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.



Safety Data Sheet

Lyden Oil Company

Page 8 of 8

PROGUARD Merit Honing Oil 20 EP

SDS Number: 17936

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 12/17/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.