

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

**1** PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD SPARGRIND EP Honing Oil  
Revision Date: 02/25/2016  
SDS Number: 802251  
Common Name: Hydrotreated petroleum oil  
CAS Number: Blend  
Product Code: 802251  
Synonyms: Machining and grinding lubricant

**Company Identification:**

*Manufactured for:*  
LYDEN OIL COMPANY  
3711 LeHarps Drive  
Youngstown, OH 44515

For Product Information: 1-330-792-1100  
For Emergencies: 1-800-424-9300  
CHEMTREC: 1-800-424-9300 or 1-703-527-3887

**2** HAZARDS IDENTIFICATIONSignal Word:**DANGER**Hazard Classes/Categories:

Aspiration hazard, Category 1.

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand.  
P102: Keep out of reach of children.  
P103: Read label before use.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331: Do NOT induce vomiting.  
P405: Store locked up.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:  
Health = 1  
Fire = 1  
Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

**3** COMPOSITION / INFORMATION ON INGREDIENTSIngredients:

*Mixture of the substances listed below with nonhazardous additions.*

Chemical Name	CAS Number	Percentage
Hydrotreated middle distillates (petroleum)	64742-46-7	80-90

*\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.*

**4** FIRST AID MEASURESDescription of First Aid Measures:

## Inhalation:

If symptoms develop, move victim to fresh air and keep in a position comfortable for breathing. If symptoms persist, obtain medical attention.

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

**Skin Contact:**

Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.

**Eye Contact:**

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult medical attention.

**Ingestion:**

If swallowed, do NOT induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Symptoms and Effects, both acute and delayed:

No further relevant data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

**5 FIRE FIGHTING MEASURES**

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

**6 ACCIDENTAL RELEASE MEASURES**

Personal Precautions:

Avoid contact with skin, eyes, and clothing.  
Keep away from sources of ignition.

Emergency Procedures:

Contain spilled material, collect in suitable and properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water course.  
Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.

**7 HANDLING AND STORAGE**

Handling Precautions:

Handle with care and avoid spillage on the floor.  
Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed.  
Keep away from sources of ignition.

**8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure Limits:

-64742-46-7 Hydrotreated Middle Distillates (petroleum) (80-90%):

ACGIH TWA – 5mg/m<sup>3</sup>

OSHA TWA – 5mg/m<sup>3</sup> (mist)

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.  
Use safety glasses and gloves.

**9** **PHYSICAL AND CHEMICAL PROPERTIES**

Color:	Amber
Physical State:	Liquid
Odor:	Characteristic
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>500° F
Boiling Range:	Data not available
Flash Point:	275° F
Evaporation Rate:	<1 (where Butyl Acetate = 1)
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.8344
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	4.8 mm <sup>2</sup> /sec (kinematic at 40° C)

**10** **STABILITY AND REACTIVITY**Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

Conditions to Avoid:

Extreme temperature, sparks, open flame, and direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

Strong oxidizers and strong reducing agents.

Decomposition Products:

Oxides of carbon, sulfur, and hydrogen.

**11 TOXICOLOGICAL INFORMATION**Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects:

May be fatal if swallowed and enters airways.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagenic.

**12 ECOLOGICAL INFORMATION**Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

**PROGUARD SPARGRIND EP Honing Oil**

SDS Number: 802251

**13 DISPOSAL CONSIDERATIONS**Disposal Methods:

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

**14 TRANSPORT INFORMATION**

<u>UN Number:</u>	Data not available
<u>UN Shipping Name:</u>	Lubricating Oil, N.O.S.
<u>Transport Hazard Class:</u>	Data not available
<u>Packing Group:</u>	Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

**15 REGULATORY INFORMATION**

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



# Safety Data Sheet

Lyden Oil Company

Page 8 of 8

## PROGUARD SPARGRIND EP Honing Oil

SDS Number: 802251

16	OTHER INFORMATION
----	-------------------

Last Revision Date: 02/25/2016

*The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.*