



# Lyden Oil Company

## ProGuard

### Product Information

---

#### **ProGuard ProCut 157SC**

**ProGuard ProCut 157SC** is a dark colored active cutting oil containing sulfur, chlorine and fat. These components make the versatile **ProCut 157SC** suitable for a wide range of ferrous metalworking applications where high speeds, smooth finishes and long tool life are important.

#### **Applications**

- Thread grinding and rolling
- Cutting
- Gear hobbing
- Broaching
- Tapping
- Turning
- Reaming
- Milling
- Forming
- Shaving

#### **Typical Properties**

##### **ProGuard ProCut 157SC**

---

Product Code Number	17950
Viscosity, cSt at 40 °C, ASTM D-445	30
Flash Point, °C (°F), ASTM D-92	157 (315)
Total Sulfur, %	1.7
Active Sulfur, %	0.8
Fat, %	7.2
Chlorine, %	1.0

---

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465  
1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarps Road  
Youngstown, OH 44515  
1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906  
1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317  
local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646  
local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com