

ProGuard Premium Blue No. 2 Grease Product Data Sheet

ProGuard Premium Blue No 2 Grease is a very tacky- lithium thickened, multi-functional extreme pressure (EP) grease formulated to withstand constant temperatures up to 250 Deg. F for extended periods of time. It is dyed blue for easy identification and is easily pumpable.

ProGuard Premium Blue No. 2 Grease is designed for heavily loaded bearing applications where water washout is a problem. Applications include steel mill bearing lubrication in tubular rolling mills and other applications that require a very tacky, premium, extreme pressure grease for heavily loaded bearings that may be exposed to high water contamination and water washing.

Benefits

- High melting point
- High load carrying ability
- Extreme pressure protection
- Protection against rust and corrosion
- Extremely water resistant
- Stays in place

Typical Characteristics

| ProGuard Premium Blue No. 2 Grease | 2 |
|---------------------------------------|-------------------|
| Base Oil Viscosity | |
| @40 Deg. C, cSt | 460 |
| Appearance | Very Tacky/Smooth |
| Dropping Point Deg. F | 365 |
| Rust Protection | Pass |
| Color | Blue |

071101

3249 Wales Ave. NW Massillon, OH 44646 (330)832-7800 fax: (330)832-2787 3711 LeHarps Rd. Youngstown, OH (800)362-9410 fax: (330)792-1462

Lyden Oil Company

2649 Tracy Rd. Northwood, OH (800)245-9336 fax: (419)666-8790 419 Spring St. Lansing, MI 48101 (800)968-6457 fax: (517)485-0605 24200 W. Outer Dr. Allen Park, MI 48912 (313)383-0097 fax: (313)383-2342