

ProGuard Sparsol CF Chlorine-free Machining, Grinding & Cutting Fluid Product Data Sheet

ProGuard Sparsol CF is an advanced, chlorine free soluble oil designed for a variety of metalworking applications. **ProGuard Sparsol CF** uses a vegetable oil based formula and contains polar lubricity agents. The product mixes easily with water and will form a good stable emulsion. **ProGuard Sparsol CF** is designed for use in light to medium metalworking applications and can be used for ferrous and nonferrous materials. Bacterial and fungal inhibitors have been built into **ProGuard Sparsol CF** to extend sump life and prevent user discomfort. **ProGuard Sparsol CF** will provide good rust protection for machine, tool and work piece. It has low foaming characteristics which makes it an ideal choice for high speed machining and grinding.

Outstanding Features

- Excellent Cooling & Lubricity
- Reduces Tool & Grinding Wheel Wear
- Provides Good Corrosion Protection
- Mixes Easily to Form a Stable Emulsion

Typical Applications Include

- Milling
- Sawing
- Roll Forming
- Grinding

Physical Specifications

Color	Amber
Odor	Characteristic
Appearance	Clear, Liquid
Viscosity @ 40°C Cst	35-55
Viscosity @ 100°F Sus	165-255
Flash Point	310°F
Specific Gravity @ 60°F	0.9335
Density (lbs/gal)	7.774

Refractometer Readings

5%	5.0
6%	6.0
7%	7.0
8%	8.0
9%	9.0
10%	10.0

071116

3249 Wales Ave. NW Massillon, OH 44646 (330)832-7800 fax: (330)832-2787 3711 LeHarps Rd. Youngstown, OH (800)362-9410 fax: (330)792-1462

Lyden Oil Company

2649 Tracy Rd. Northwood, OH (800)245-9336 fax: (419)666-8790 419 Spring St. Lansing, MI 48101 (800)968-6457 fax: (517)485-0605 24200 W. Outer Dr. Allen Park, MI 48912 (313)383-0097 fax: (313)383-2342