



Lyden Oil Company

ProGuard

Product Information

ProGuard UltraPar Series

ProGuard UltraPar oils are manufactured from high viscosity index paraffinic oils that are inherently stable under moderate operating conditions. These oils exhibit good demulsibility and resist foaming from aeration.

ProGuard UltraPar oils are recommended for lubrication in a wide range of applications including: certain internal combustion engines, hydraulic systems, gear boxes, plain and anti-friction bearings, electric motors, vacuum pumps, air and gas compressors, chain drives, machine tools and mill roll bearings.

Typical Properties

ProGuard

UltraPar Series	5	10	15	22	32	68
Product Code Number	17820	11702	11706	11704	11705	17831
Viscosity, ASTM D-445						
cSt at 100 °C	1.8	2.7	3.2	4.0	5.0	8.4
cSt at 40 °C	5.1	10.6	14.8	20.2	28.7	64.5
Viscosity Index	84	87	92	97	99	95
Flash Point, ASTM D-92						
°C (°F)	150 (302)	177 (350)	179 (355)	207 (405)	210 (410)	249 (480)
Pour Point, ASTM D-5950						
°C (°F)	-17 (0)	-17 (0)	-17 (0)	-17 (0)	-17 (0)	-15 (5)
API Gravity	36.0	35.0	34.0	33.0	32.1	29.0
Color	0.5	0.5	1.0	1.0	0.5	2.5

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com