



# Lyden Oil Company

## ProGuard

### Product Information

---

#### **ProGuard ProCut 65S**

**ProGuard ProCut 65S** is a light colored active cutting oil containing active sulfur and fat. It is an excellent choice for threading, tapping and internal grinding.

**ProGuard ProCut 65S** provides excellent surface finishes.

#### **Applications:**

- Threading
- Cutting
- Tapping
- Internal Grinding

#### **Typical Physical Characteristics:**

##### **ProGuard ProCut 65S**

---

Product Code Number	17801
Viscosity, ASTM D-88 SUS at 100° F	65
Flash Point, ASTM D-92, °F (°C)	350 (176)
Specific Gravity, at 60° F	0.869
Sulfur, %	2.0
Active Sulfur, %	1.9
Fat, %	5.0
Chlorine, %	Nil
Volatile Organic Compounds	Nil

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465

1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarps Drive  
Youngstown, OH 44515

1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906

1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317

local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646

local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com