

Lyden Oil Company

Page 1 of 8 -

1

PROGUARD SPARKUT BR

SDS Number: 804181

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD SPARKUT BR
Revision Date:	04/18/2016
SDS Number:	804181
Common Name:	Sulfurized Hydrocarbon
CAS Number:	Blend
Product Code:	804181
Synonyms:	Active Sulfur Cutting Oil

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page 2 of 8 -

PROGUARD SPARKUT BR

SDS Number: 804181

Other Hazard Statement(s):

-NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>70

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:	
	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
Skin Contact:	
	Flush skin with water, wash with soap and water. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment.
Eye Contact:	
	Flush eyes with running water for at least 15 minutes. If redness, blurred vision or irritation persists, transport to nearest medical facility for additional treatment.



PROGUARD SPARKUT BR

Lyden Oil Company

SDS Number: 804181

Ingestion:

Do NOT induce vomiting and obtain medical attention. Have victim rinse mouth out with water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES **Recommended Fire-Extinguishing Equipment:** Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters. Possible Hazards During a Fire: Procedures for an oil fire should be followed. **Recommendations to Firefighters:** Use self-contained breathing apparatus. Use foam or dry chemical to extinguish fire. Water may be used only to keep surrounding containers cool. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Page **3** of **8** —



PROGUARD SPARKUT BR

Lyden Oil Company

SDS Number: 804181

6 ACCIDENTAL RELEASE MEAS	SURES
Personal Precautions:	
	Avoid eye contact. Avoid repeated or prolonged skin contact. Personal protective equipment must be worn. Avoid contact with skin, eyes or clothing. Keep unprotected persons away.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course.
<u>Cleanup Procedures:</u>	Do not allow to enter ground waters. Pick up excess with inert absorbant material.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
Storage Requirements:	Keep container tightly sealed. Keep away from sources of ignition.

Page **4** of **8** -



PROGUARD SPARKUT BR

Lyden Oil Company

SDS Number: 804181

Page 5 of 8 -

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

8

-Distillates (petroleum), hydrotreated naphthenic:

OSHA TWA – 5mg/m³ (oil mist)

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color:	Dark-Brown
Physical State:	Liquid
Odor:	Sulfur-like
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>500° F
Boiling Range:	Data not available
Flash Point:	360° F
Evaporation Rate:	<1
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.943
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available



Page 6 of 8 —

Safety Data Sheet

Lyden Oil Company

		PROGUARD SPARKU	T BR
SDS Number: 80	4181		
Decomposition Viscosity:	Temperature:	Data not available 38 mm²/sec (kinematic at 40° C)	
10	STABILITY AND REA	CTIVITY	
<u>Stability:</u>		Stable under normal conditions.	
<u>Reactivity:</u>		Not reactive under normal conditions.	
Conditions to Av	<u>/oid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.	
<u>Hazardous Reac</u>	tions:	No known hazardous reactions.	
Incompatible M	aterials:	Strong oxidizers and strong reducing agents.	
Decomposition	Products:	Oxides of carbon, sulfur, and hydrogen.	

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	This mixture can cause irritation, redness to the eyes. Prolonged and/or repeated skin contact may cause irritation/dermatitis. May be fatal if swallowed and enters airways. Aspiration hazard.
	Mists and vapors may cause respiratory irritation , drowsiness and dizziness.



PROGUARD SPARKUT BR

Lyden Oil Company

SDS Number: 804181

Page 7 of 8 -

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

ds:

Disposal Containers:

Use properly approved container for disposal.

Dispose of waste material in accordance with all

Special Precautions:

14

Do not flush to surface waters or drains.

local, state, and federal requirements.

TRANSPORT INFORMATION

<u>UN Number:</u>	Data not available
UN Shipping Name:	Data not available
Transport Hazard Class:	Data not available
Packing Group:	Data not available

Environmental Hazards:

Data not available



Lyden Oil Company

Page **8** of **8** –

PROGUARD SPARKUT BR

SDS Number: 804181

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION

Last Revision Date: 04/18/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.