

Lyden Oil Company

Page **1** of **8** —

1

### **PROGUARD SPARGRIND 60**

SDS Number: 809081

### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD SPARGRIND 60
Revision Date:	09/08/2015
SDS Number:	809081
Common Name:	Heavy paraffinic oil
CAS Number:	Blend
Product Code:	809081
<u>Synonyms:</u>	Petroleum based lubricant, Cutting and grinding fluid

#### **Company Identification:**

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

### HAZARDS IDENTIFICATION



Signal Word:

2

Hazard Classes/Categories:

DANGER

Aspiration hazard, Category 1.

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.



Lyden Oil Company

Page 2 of 8 -

### **PROGUARD SPARGRIND 60**

SDS Number: 809081

Precaution Statement(s):P101: If medical advice is needed, have product container or label at<br/>hand.P102: Keep out of reach of children.P103: Read label before use.P301+310: IF SWALLOWED: Immediately call a POISON<br/>CENTER/doctor.P331: Do NOT induce vomiting.P405: Store locked up.P501: Dispose of contents/container in accordance with<br/>local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	<95

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.



**PROGUARD SPARGRIND 60** 

Lyden Oil Company

SDS Number: 809081

## 4 FIRST AID MEASURES Description of First Aid Measures: Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility. Skin Contact: Flush skin with water, wash with soap and water. Remove contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. Eye Contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention. Ingestion: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Symptoms and Effects, both acute and delayed: No further relevent data available. **Recommended Actions:** Treat symptomatically. Call a doctor or poison control center for guidance. 5 FIRE FIGHTING MEASURES **Recommended Fire-Extinguishing Equipment:**

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.

Page **3** of **8** –



Lyden Oil Company

## Page 4 of 8 -**PROGUARD SPARGRIND 60** SDS Number: 809081 Possible Hazards During a Fire: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. **Recommendations to Firefighters:** Proper protective equipment including breathing apparatus. 6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labled containers. **Environmental Precautions:** Do not allow to reach sewage system or any water course. Do not allow to enter ground waters. **Cleanup Procedures:** Pick up excess with inert absorbant material. Treat contaminated absorbent same as spilled product. HANDLING AND STORAGE 7

Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.



**PROGUARD SPARGRIND 60** 

Lyden Oil Company

#### SDS Number: 809081

Page 5 of 8 -

Storage Requirements:

Keep container tightly sealed. Keep away from sources of ignition.

#### EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Limits:**

8

-64742-53-6 Distillates (petroleum), hydrotreated light naphthenic:

ACGIH TWA – Long-term value: 5mg/m<sup>3</sup> OSHA TWA – Long-term value: 5mg/m<sup>3</sup> (mist)

#### **Engineering Controls:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

#### 9

#### PHYSICAL AND CHEMICAL PROPERTIES

Color:	Pale Yellow
Physical State:	Liquid
Odor:	Characteristic
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>500° F
Boiling Range:	Data not available
Flash Point:	460° F
Evaporation Rate:	<1 (where Butyl Acetate - 1)
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water



**PROGUARD SPARGRIND 60** 

Lyden Oil Company

#### SDS Number: 809081

Page 6 of 8 -

Partition Coefficient:
Auto-Ignition Temperature:
Decomposition Temperature:
Viscosity:

Data not available Data not available Data not available 9.0 mm²/sec (kinematic at 40° C)

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to A	<u>Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
<u>Hazardous Rea</u>	ictions:	No known hazardous reactions.
Incompatible N	<u>Materials:</u>	Strong oxidizers and strong reducing agents.
<u>Decomposition</u>	n Products:	Oxides of carbon and hydrogen.
11	TOXICOLOGICAL INFORMATIO	Ν

Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an
	oil acne.



**PROGUARD SPARGRIND 60** 

Lyden Oil Company

SDS Number: 809081

Page 7 of 8 -

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagentic.

### 12 ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.

**Ecological Effects:** 

No specific environmental or aquatic data available.

#### 13 DISPOSAL CONSIDERATIONS

**Disposal Methods:** 

Disposal Containers:

Use properly approved container for disposal.

Dispose of waste material in accordance with all

Special Precautions:

14

Do not flush to surface waters or drains.

local, state, and federal requirements.

#### TRANSPORT INFORMATION

<u>UN Number:</u>
UN Shipping Name:
Transport Hazard Class:
Packing Group:

Data not available Lubricating Oil, N.O.S. Data not available Data not available

Environmental Hazards:

Data not available



Lyden Oil Company

Page **8** of **8** –

## **PROGUARD SPARGRIND 60**

SDS Number: 809081

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 0	OTHER INFORMATION
------	-------------------

Last Revision Date: 09/08/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.