

Lyden Oil Company

Page **1** of **8** –

1

PROGUARD Hi Mileage 0W-20 Motor Oil

SDS Number: 712011

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Hi Mileage 0W-20 Motor Oil
Revision Date:	12/01/2015
SDS Number:	712011
Common Name:	Heavy paraffinic oil/Synthetic base oils
CAS Number:	Blend
Product Code:	712011
<u>Synonyms:</u>	SN/GF-5 passenger car motor oil

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Hi Mileage 0W-20 Motor Oil

SDS Number: 712011

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	0-100
Residual oils (petroleum), solvent refined	64742-01-4	0-100
Residual oils (petroleum), hydrotreated	64742-57-0	0-100
Residual oils (petroleum), solvent dewaxed	64742-62-7	0-100
Lubricating oils (petroleum), C>25, hydrotreated bright stock	72623-83-7	0-100
Lubricating oils (petroleum), C20-C50, hydrotreated neutral	72623-87-1	0-40
oil-based	178603-64-0	0-45
Gas oils (petroleum), hydrocracked, C15-C30, branched and	178603-65-1	0-45
cyclic, high VI	178603-66-2	0-45
Gas oils (petroleum), hydrocracked, C20-C40, branched and	N/A	4-24
cyclic, high VI	64742-52-5	0-26
Gas oils (petroleum), hydrocracked, C25-C55, branched and	68649-42-3	0.25-1.5
cyclic, high VI		
Mineral Oil		
Petroleum distillates, hydrotreated heavy naphthenic		
Phosphorodithioic acid, O,O-di-C1-C14-alkyl esters, zinc salts		

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.



Safety Data Sheet

Lyden Oil Company

Page 3 of 8		
	PROGUARD Hi Mileage 0W-20 Motor Oil	
SDS Number: 712011		
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.	
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.	
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.	
Symptoms and Effects, both a	<u>cute and delayed:</u> No further relevent data available.	
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.	
5 FIRE FIGHTI	NG MEASURES	
Recommended Fire-Extinguish	ning Equipment: Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.	
Possible Hazards During a Fire	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.	
Recommendations to Firefight	ters: No special measures required.	



PROGUARD Hi Mileage 0W-20 Motor Oil

Lyden Oil Company

SDS Number: 712011

6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labeled containers. **Environmental Precautions:** Do not allow to reach sewage system or any water course. Do not allow to enter ground waters. Cleanup Procedures: Pick up excess with inert absorbant material. HANDLING AND STORAGE 7 Handling Precautions: Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container. Storage Requirements: Keep container tightly sealed. Keep away from sources of ignition. **EXPOSURE CONTROLS / PERSONAL PROTECTION** 8 Exposure Limits: **Engineering Controls:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Page **4** of **8** –



Lyden Oil Company

Page 5 of 8 -

9

PROGUARD Hi Mileage 0W-20 Motor Oil

SDS Number: 712011

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber
Physical State:	Liquid
Odor:	Petroleum
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	246° C / 475° F
Boiling Range:	Data not available
Flash Point:	190° C / 380° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	<1 mmHg at 20° C
Vapor Density:	Data not available
Relative Density:	7.16 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	8.5 mm ² /sec (kinematic at 100° C)

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to Av	void:	Extreme temperature, sparks, open flame, and direct sunlight.



Lyden Oil Company

Page 6 of 8			
C C C C C C C C C C C C C C C C C C C	PROGUARD Hi Mileage 0W-20 Motor Oil		
SDS Number: 712011			
Hazardous Reactions:	No known hazardous reactions.		
Incompatible Materials:	No further relevant information available.		
Decomposition Products:	Hazardous decomposition products are not expected to form.		
11 TOXICOLOGICAL INFORMATIO	Ν		
Routes of Exposure:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.		
Exposure Effects:	Repeated skin contact may cause dermatitis or an oil acne.		
Measures of Toxicity:	No test data available.		
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.		
12 ECOLOGICAL INFORMATION			
Ecological Precautions:	Avoid exposing to the environment.		
Ecological Effects: No specific environmental	l or aquatic data available.		



PROGUARD Hi Mileage 0W-20 Motor Oil

Lyden Oil Company

SDS Number: 712011

Page 7 of 8 -

13	DISPOSAL CONSIDERATIONS	
Disposal Methods	<u>.</u>	Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containe	<u>rs:</u>	Use properly approved container for disposal.
Special Precaution	<u>ıs:</u>	Do not flush to surface waters or drains.
14	RANSPORT INFORMATION	
<u>UN Number:</u> <u>UN Shipping Name</u> <u>Transport Hazard</u> <u>Packing Group:</u>		
Environmental Ha	zards:	Data not available
<u>Bulk Transport Gu</u>	idance:	Data not available
Special Precaution	<u>ıs:</u>	Not regulated by DOT.
15 F	REGULATORY INFORMATION	

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Hi Mileage 0W-20 Motor Oil

SDS Number: 712011

16

Last Revision Date: 12/01/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.