



Lyden Oil Company

Product Information

Brake Wash V

Lyden Oil Company's **Brake Wash V** is a non-chlorinated solvent blend ideal for cleaning and degreasing of brake discs, pads, and many metallic surfaces. It can be applied by brush, wiping, dip, or spray and dries fast to leave a clean, un-wetted surface. It helps solubilize and remove most oils, greases, dirt/dust particulate, carbon deposits, and other soils. **Brake Wash V** is also useful for cleaning electrical contacts, shop tools, and for cleaning metallic parts.

Typical Properties

Brake Wash V

Appearance	Clear
Color, Pt-Co scale	15 max
Density @ 60 °F, Lb/Gal, ASTM D-287	6.15
Flash Point (TCC), °F, ASTM D-56	< 0.4
Specific Gravity (60/60 °F), ASTM D-287	0.728-0.748

**CAUTION: Brake Wash V is a flammable liquid, do not use around sparks or open flame. Use only in a well ventilated area. May soften some plastics and paints, test material compatibility for use.*

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com