



Lyden Oil Company

ProGuard

Product Information

ProGuard UltraNap Series

ProGuard UltraNap are manufactured from select naphthenic-based crude oils characterized by their low pour points and good solvency properties.

ProGuard UltraNap oils are medium solvency oils with a high degree of additive acceptance. Applications include printing inks, textile conditioning, leather tanning, turbine flushing, rust-proofing compounds, process oils and dust suppressants.

Typical Properties

ProGuard UltraNap Series	22	32	46	68	100	150
Viscosity,						
SUS at 100 °F	107	155	210	310	520	775
SUS at 210 °F	38	41	44	49	53	61
Viscosity Index	43	44	46	52	56	60
Flash Point, ASTM D-92						
°C (°F)	168 (335)	177 (350)	179 (355)	207 (405)	210 (410)	218 (425)
Pour Point, ASTM D-5950						
°F	-40	-25	-20	-15	-5	0
API Gravity	24.5	23.5	23.2	22.5	21.8	21.4
Color	0.5	0.5	0.5	1.0	1.0	1.5
Aniline Point, °F	162	162	166	168	172	178

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com