

Lyden Oil Company ProGuard

Product Information

ProGuard CS Steel Mill Grease

ProGuard CS Steel Mill Grease is a high performance grease designed with a unique calcium sulfonate thickening agent with extreme pressure additives for applications where great protection from water washout, high heat dropping points, and extreme heavy and shock load protection is desired while providing excellent pumpability.

ProGuard CS Steel Mill Grease is formulated especially for use in steel mills and other industrial applications requiring an extreme pressure grease that will be exposed to high heat and moisture, while maintaining pumpability through centralized systems. It may also be used in off-road equipment applications requiring a water resistant, EP grease.

Benefits

- · High dropping point
- Excellent water resistance
- Exhibits outstanding shear stability
- Provides protection against rust and corrosion
- Excellent pumpability
- Great heavy and shock load carrying ability

ProGuardCS Steel Mill Grease

NLGI Grade
Thickener
Color
Appearance
Dropping Point, °F, ASTM D2265
Base Oil Viscosity, cSt @ 40°C, ASTM D445
Timken OK Load, lbs. ASTM D2509
Four Ball Wear, mm, ASTM D2266
Four Ball EP Weld Pt, kg, ASTM D2596
Copper Corrosion, ASTM D130
Water Washout, % Loss, ASTM D1264
Rust Prevention, ASTM D1743
Cone Penetration @ 77°F, ASTM D217
worked 60

worked 60 Molybdenum Disulfide, wt.% #1 (W)

Calcium Sulfonate

Grey Smooth 620+ 150 60 min. 0.4 800 Pass 1.0 Pass

310-340

1

Page 1 2.4.2019

Lyden Oil Company

30692 Tracy Road Walbridge, OH 434651(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road Youngstown, OH 44515 1(800)362-9410 local: (330)792-1100 fax: (330)792-1462 lal@lydenoil.com 16275 National Parkway Lansing, MI 48906 1/800)968-6457

1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com Shelby Township, MI 48317 local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com

8151 Millis Road

3249 Wales Ave. NW Massillon, OH 44646local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com