

ProGuard EP Gear Oils (Lighter Grades)

ProGuard EP Gear Oils are designed to surpass the performance of currently available industrial gear oil products. They are thermally stable and provide an extreme pressure additive system to protect the equipment against wear and micro-pitting, and to prevent the formation of sludge. EP protection is maintained in these lighter ISO viscosity grades for equipment requiring a low-viscosity gearbox oil or a light circulating oil with extreme pressure additives. They provide outstanding wear protection, cleanliness, sludge prevention and water separation.

DIN 51517-3 CLP ISO 12925-1 CKC/CKD AGMA 9005-E02 EP **Typical Properties** ProGuard **EP Gear Oils** 32 46 AGMA Number 1 E P n/a Viscosity, ASTM D-445 cSt at 40 °C 33 45 cSt at 100 °C 5.4 6.9 Viscosity Index, ASTM D-2270 99 99 Flash Point, (COC) ° F, ASTM D-92 410 420 Pour Point, ° F, ASTM D-97 -18 -18 Timken OK Load, lb., ASTM D-2782 65 65 4-Ball EP Test, ASTM D-2783 Load-wear Index, kg 57 57 Weld Point, kg 400 400 4-Ball Wear Test, 20 kg, ASTM D-2266 1 hr, 1800 rpm, 54° C, wear scar diameter, mm 0.27 0.27 FZG Gear Test, Stages 12 12 Demulsibility, ASTM D-2711 Total Free Water, ml 85 85 Water in Oil, ml 0 0 Emulsion, ml 0.3 0.3 PASS PASS Rust Test, ASTM D-665A/B Copper Strip Corrosion, ASTM D-130 1A 1A Foam Test, Foam Vol, ml, ASTM D-892 0/0 0/0

Specifications

30692 Tracy Road Walbridge, OH 43465 1(800)24-LYDEN local: (419)666-1948 fax: (419)666-8790 gam@lydenoil.com **3711 LeHarps Road Youngstown, OH 44515** 1(800)362-9410 local: (330)792-1100 fax: (330)792-1462 lal@lydenoil.com

Lyden Oil Company

16275 National Parkway Lansing, MI 48906 1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com

www.LydenOil.com

8151 Millis Road Shelby Township, MI 48317 local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com 3249 Wales Ave. NW Massillon, OH 44646 local: (330)832-7800 fax: (330)832-2787 lal@lydenoil.com

4.7.2022

Page 1