

Lyden Oil Company ProGuard

Product Information

ProGuard Full Synthetic 0W-20 Motor Oil

ProGuard Full Synthetic Passenger Car Motor Oil OW-20 is made from synthetic base stocks for better fuel economy and reduced harmful emissions using advanced detergent-dispersant, antioxidant, anti-wear agent, friction modifier, and defoamant additives for better wear protection. This oil provides excellent protection against sludge, engine rust and corrosion, resist oil thickening by providing enhanced oxidation control under severe service conditions and low temperature operating conditions.

ProGuard Full Synthetic Passenger Car Motor Oil 0W-20 is suitable for use in all seasons in all makes and models of gasoline engines requiring an API specification SP or ILSAC GF-6, 0W-20 viscosity engine oil, including vehicles manufactured by Ford, Chrysler, Honda, Acura, Subaru, Mitsubishi, Hyundai, and Kia.

Typical Properties

ProGuard

Full Synthetic Passenger Car Motor Oil	0W-20	
Product Code Number	504161	
Viscosity, ASTM D-445		
cSt at 100 °C	8.2	
cSt at 40 °C	43.4	
Viscosity Index	166	
Cold Cranking Viscosity, ASTM D-5293		
cP at Temp °C	5,800 at -35	
NOACK Volatility, % wt. loss, ASTM D-5800	13.9	
High Temp/High Shear Visc., ASTD D-4683		
cP at 150 °C	2.7	
Pour Point, °C (°F), ASTM D-5950	-51 (-59)	
Maximum API / ILSAC Performance	SP/GF-6A	

Page 1 5.14.2020

30692 Tracy Road Walbridge, OH 434651(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road Youngstown, OH 445151(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

Lyden Oil Company 16275 National Parkway

Lansing, MI 48906 1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com 8151 Millis Road Shelby Township, MI 48317 local: (586)997-1319

local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com **3249** Wales Ave. NW Massillon, OH 44646 local: (330)832-7800 fax: (330)832-2787 lal@lydenoil.com