

## **Lyden Oil Company ProGuard**

## **Product Information**

## **ProGuard SHL Racing Motor Oil**

**ProGuard** SHL Racing Motor Oils are select automotive lubricants formulated to meet or exceed the requirements of high performance engines that require higher zinc contents to protect critical engine parts.

**ProGuard** SHL Racing Motor Oils are specially formulated with synthetic base oils and advanced additives to protect in the extreme conditions found in the racing environment. It provides excellent protection against friction, wear and oxidation even at highly elevated temperatures. It also contains dispersant additives which make for effective deposit control. It meets or exceeds the requirements of API SN and all previous categories, including SM, SL and SJ, but contains more than the maximum amounts of zinc and phosphorus allowed by ILSAC.

## Typical Properties **ProGuard**

rioduaiu				
SHL Racing Motor Oil		5W-20	5W-30	10W-30
Viscosity, ASTM D-445				
cSt at 100 °C		8.5	10.8	10.5
cSt at 40 °C		46.8	71.5	68.9
Viscosity Index		160	140	140
Cold Cranking Viscosity, ASTM D-5293				
cP at Temp °C		5,500 at -30	5,500 at -30	5,400 at -25
HTHS Viscosity, cP, ASTM D-4683		2.6	3.1	3.1
Pour Point, °C (°F), ASTM D-5950		-47 (-52)	-42 (-43)	-36 (-32)
NOACK Volatility, % wt. loss, ASTM D-5800		13	12	8
Total Base Number, ASTM [	D-2896			
mg KOH/g		8.3	8.3	8.3
Zinc, ppm		2000	2000	2000

Page 1 7.9.2021

**30692 Tracy Road Walbridge, OH 43465**1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road Youngstown, OH 44515 1(800)362-9410 local: (330)792-1100 fax: (330)792-1462 lal@lydenoil.com **Lyden Oil Company** 16275 National Parkway Lansing, MI 48906

1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com 8151 Millis Road Shelby Township, MI 48317

local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com **3249 Wales Ave. NW Massillon, OH 44646**local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com