



Lyden Oil Company

ProGuard

Product Information

ProGuard Merit Honing Oil #5, #10

ProGuard Merit Honing Oil is a low viscosity, transparent fluid used in a wide variety of honing operations. It contains a fatty oil making it ideal for operations requiring superior finish.

ProGuard Merit Honing Oil is free cutting without loading the stones and provides a high degree of cooling.

Benefits

- Improved surface finish
- Eliminates scoring
- Minimized stone cracking

ProGuard

Merit Honing Oil

	#5	#10
Product Code	102151	102152
Viscosity, ASTM D-2161 SUS @ 100° F	42	54
Flash Point, ASTM D-92, ° F	250	275
Fat, %	5.0	10.0
Copper Corrosion, ASTM D-130	No Stain	No Stain

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com