



# Lyden Oil Company

## ProGuard

### Product Information

#### ProGuard Merit Honing Oils

**ProGuard Merit Honing Oil** is a low viscosity, transparent fluid used in a wide variety of honing operations. It contains a fatty oil making it ideal for operations requiring superior finish.

**ProGuard Merit Honing Oil** is free cutting without loading the stones and provides a high degree of cooling.

**ProGuard Merit Honing Oil 20EP** contains additional sulfurized additives and a high amount of lubricity agent, making it ideal for severe honing operations.

#### Benefits

- Improved surface finish
- Eliminates scoring
- Minimized stone cracking

#### ProGuard

#### Merit Honing Oil

	5	10	20EP
Product Code	102151	102152	17936
Viscosity, ASTM D-2161 SUS @ 100° F	42	54	78
Flash Point, ASTM D-92, ° F	250	275	275
Fat, %	5.0	10.0	20.0
Active Sulfur, %	Nil	Nil	2.4
Copper Corrosion	No Stain	No Stain	May Stain

#### Lyden Oil Company

30692 Tracy Road  
Walbridge, OH 43465  
1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarps Road  
Youngstown, OH 44515  
1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906  
1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317  
local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646  
local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com