

Lyden Oil Company ProGuard

Product Information

ProGuard Merit Non-Stain Hydraulic Fluid

ProGuard Merit Non-Stain Hydraulic Fluid is a specially formulated hydraulic fluid designed for use in hydraulic systems at aluminum rolling operations. It provides superior oxidation resistance and corrosion protection. It contains ashless additives and base oils that minimize staining of aluminum surfaces, while providing an excellent level of protection for the hydraulic system.

ProGuard Merit Non-Stain Hydraulic Fluid is compatible with most rolling oils, allowing for continuous operation.

Typical Properties

ProGuard

Merit Non-Stain Hydrau	lic Fluid	32
Product Code Number		17924
ISO Viscosity Grade		32
Viscosity, ASTM D-445		
cSt at 40 °C		33.0
Flash Point, °C (°F), ASTM	I D-92	110 (230)
Specific Gravity		0.820
Vane Pump Test		
Ring Loss, g		0.002
Vane Weight Loss, g		0.017
Total Loss, g		0.019
Rust Test, Salt Water, ASTM D-665 Pass		Pass
Copper Strip, 3 hrs at 212	2°F	1b

8.16.2016 Page 1

30692 Tracy Road Walbridge, OH 43465

1(800)24-LYDEN local: (419)666-1948 fax: (419)666-8790 gam@lydenoil.com

3711 LeHarps Road Youngstown, OH 44515 1(800)362-9410 local: (330)792-1100 fax: (330)792-1462 lal@lydenoil.com

Lyden Oil Company 16275 National Parkway

> Lansing, MI 48906 1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com

8151 Millis Road Shelby Township, MI 48317 local: (586)997-1319

fax: (586)997-1352 jcc@lydenoil.com

3249 Wales Ave. NW Massillon, OH 44646 local: (330)832-7800 fax: (330)832-2787 lal@lydenoil.com