



Lyden Oil Company

ProGuard

Product Information

ProGuard RP 10WD

ProGuard RP 10WD is an all-purpose rust preventive that is exceptionally stable in wet conditions. It provides rapid displacement and separation of water and leaves an excellent thin film protection.

ProGuard RP 10WD meets the requirements of Federal Specification VV-L-800A and Military Specification MIL-63460-70.

Typical Properties

ProGuard RP 10WD

| | |
|---------------------------------------|---------------------|
| Recommended Film Thickness | 0.10 mils |
| Film Type | Transparent, Oily |
| Color, ASTM D- | |
| Theoretical Coverage | 1900 sq. ft./gallon |
| Water Displacement, (MIL-C-16173D) | PASS |
| Flash Point, °C (°F), ASTM D-92 | >93° (>200°) |
| Humidity Cabinet, 120 °F, ASTM D-1748 | 30 day min. |
| Indoor Storage | Up to one year |

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarp's Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com