



# Lyden Oil Company

## ProGuard

### Product Information

#### **ProGuard SparMist Band Saw Oil LT**

**ProGuard SparMist Band Saw Oil LT** is a highly refined, naphthenic petroleum basestock blended with a vegetable derived lubricity additive that not only lubricates the cutting blade but also prevents the build-up of sticky resinous material. It is also fortified with extreme pressure agents for longer lasting tool life while helping to keep the blade clean.

**ProGuard SparMist Band Saw Oil LT** utilizes a thinner base stock which is optimized for low temperature use and for misting applications.

#### Typical Properties

##### **ProGuard SparKool HD**

Product Code Number	811031
Color	Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	0.8974
Density, lbs/gal	7.476
Flash Point, °C (°F)	168 (335)
Viscosity, cSt @ 40 °C	25

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465  
1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarms Road  
Youngstown, OH 44515  
1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906  
1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317  
local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646  
local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com