



Lyden Oil Company

ProGuard

Product Information

ProGuard Saw Guide Lube

ProGuard Saw Guide Lube is a totally synthetic fluid designed for micro mist type fluid delivery systems. This product is intended to be used as received (no dilution necessary). It is a suitable for a wide range of applications including metal cutting and metal forming of ferrous and non-ferrous materials.

ProGuard Saw Guide Lube may be used in any metal cutting or forming operation where minimal fluid use is required.

Advantages

Superior Lubricity
Sulfur-Free
Clings to Tool
Virtually No Disposal Concerns
Economical- Micro Mist Dispensing Uses Only Ounces Per Day

Phosphorous-Free
Chlorine-Free
For Ferrous and Non-Ferrous Metals

Typical Properties

ProGuard Saw Guide Lube

Appearance	Transparent Blue Liquid
Residual Film	Slight
Specific Gravity at 60 °F	0.82
Viscosity, cSt at 40 °C	16
Flash Point, °C (°F), ASTM D-92	222 (432)
Total Sulfur, %	None
Phosphorus, %	None
Chlorine, %	None

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com