



Lyden Oil Company

ProGuard

Product Information

ProGuard SparDraw 124

STAMPING AND DRAWING LUBRICANT

ProGuard SparDraw 124 is a medium viscosity metal forming oil that can be used in drawing, stamping, and fine blanking operations. This oil contains lubricity boosters and is heavily fortified with extreme pressure (EP) additives. It also contains a rust preventative for in-process protection.

Typical Properties

ProGuard SparDraw 124

Product Code Number	806256
Color	Golden Yellow
Odor	Characteristic
Appearance	Clear Liquid
Viscosity, ASTM D-445	
cSt at 40 °C	70-110
SUS at 100 °F	325-510
Flash Point, °F	> 240
Specific Gravity, ASTM D-1298	1.10
Density, lbs/gal	7.811

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com