



Lyden Oil Company

ProGuard

Product Information

ProGuard SparDraw 263

FORMING AND DRAWING LUBRICANT

ProGuard SparDraw 263 is a medium viscosity forming oil containing lubricity and extreme pressure (EP) additives. This product contains chlorine and sulfur and it is specifically designed for medium to heavy duty deep drawing operations.

Typical Properties

ProGuard SparDraw 263

Product Code Number	809171
Color	Brown
Odor	Characteristic
Appearance	Clear Liquid
Viscosity, ASTM D-445	
cSt at 40 °C	60-72
SUS at 100 °F	277-333
Flash Point, °F	> 330
Specific Gravity, ASTM D-1298	0.9831
Density, lbs/gal	8.189

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com