



Lyden Oil Company

ProGuard

Product Information

ProGuard SparDraw 442

STAMPING, DRAWING AND BLANKING LUBRICANT

ProGuard SparDraw 442 is an extremely heavy duty drawing and stamping oil. **SparDraw 442** contains a high level of extreme pressure additives which are effective in prolonging the life of the draw die. This product can be used on cold rolled steel, stainless steel and other alloys. It contains surfactant to help facilitate downstream cleaning.

Typical Properties

ProGuard SparDraw 442

Product Code Number	806255
Color	Amber
Odor	Characteristic
Appearance	Clear Liquid
Viscosity, ASTM D-445	
cSt at 40 °C	1400-1900
SUS at 100 °F	6500-8800
Flash Point, °F	> 350
Specific Gravity, ASTM D-1298	1.208
Density, lbs/gal	10.07

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com