

ProGuard SparDraw Syn 468

SYNTHETIC DRAWING LUBRICANT

ProGuard SparDraw Syn 468 is a heavy duty drawing and stamping fluid. It is formulated with EP and polar lubricity agents to handle medium to heavy ferrous stamping and drawing applications, and contains inhibitors to deter the formation of corrosion on the finished part. This product may be used as received or diluted with water.

Typical Properties

DroGuard	
ProGuard SparDraw Syn 468	
Product Code Number	807031
Color	Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	1.057
Density, lbs/gal	8.80
Ph (diluted 10:1)	9.30
Refractometer Readings, brix	3.8 at 5%
	7.6 at 10%
	23.0 at 25%

Page 1

7.3.2018

Lyden Oil Company

 3711 LeHarps Road
 16275 National Parkway

 Youngstown, OH 44515
 Lansing, MI 48906

 1(800)362-9410
 1(800)968-6457

 local: (330)792-1100
 local: (517)485-2285

 fax: (330)792-1462
 fax: (517)485-0605

 lal@lydenoil.com
 jtr@lydenoil.com

www.LydenOil.com

8151 Millis Road Shelby Township, MI 48317 local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com 3249 Wales Ave. NW Massillon, OH 44646 local: (330)832-7800 fax: (330)832-2787 lal@lydenoil.com

30692 Tracy Road Walbridge, OH 43465 1(800)24-LYDEN local: (419)666-1948 fax: (419)666-8790 gam@lydenoil.com

H 43465 Yo YDEN 66-1948 I 66-8790 oil com