



Lyden Oil Company

ProGuard

Product Information

ProGuard SparKool 750C

SEMI-SYNTHETIC MACHINING AND GRINDING COOLANT

ProGuard SparKool 750C is a multipurpose semi-synthetic machining and grinding coolant. 750C has superior cooling and wetting properties that result in longer tool & wheel life and can be used on a variety of ferrous and non-ferrous metals, including stainless steel and aluminum.

Typical use dilutions are 5 to 10% in water.

Typical Properties

ProGuard SparKool 750C

Color	Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	1.00
Density, lbs/gal	8.329
Ph (diluted 10:1)	9.20-9.70
Pour Point, °F	32
Refractometer Readings, brix	3.25 at 5% 6.5 at 10%

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com