

Lyden Oil Company ProGuard

Product Information

ProGuard SparKool CF

SEMI-SYNTHETIC MACHINING AND GRINDING COOLANT

ProGuard SparKool CF is a multipurpose, chlorine-free semi-synthetic machining and grinding coolant. It has superior cooling and wetting properties that result in longer tool & wheel life and can be used on a variety of ferrous and non-ferrous metals, including stainless steel and aluminum. Typical use dilutions are 5 to 10% in water.

ProGuard SparKool CF is an economical yet versatile coolant that covers a wide range of applications while avoiding the use of chlorine. It contains an excellent anti-bacterial and anti-fungal additive and will help prevent rusting of your machine tool and work piece.

Typical Applications	Milling		Turning
	Grinding		Sawing
Refractometer Readings, bris	K	3.25 a 6.50 a	
Typical Properties		9.75 a	t 15%

Typical Properties

Product Code Number

ProGuardSparKool CF

Chlorine

Color	Amber
Odor	Characteristic
Appearance	Clear Liquid
pecific Gravity, ASTM D-1298 0.9835	
Density, lbs/gal	8.19
Ph (diluted 10:1)	9.45
Pour Point, °F	32

Page 1 8.29.2018

802293

Nil

Lyden Oil Company

30692 Tracy Road Walbridge, OH 434651(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road Youngstown, OH 445151(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway Lansing, MI 48906 1(800)968-6457

1(800)968-6457 local: (517)485-2285 fax: (517)485-0605 jtr@lydenoil.com

www.LydenOil.com

Shelby Township, MI 48317 local: (586)997-1319 fax: (586)997-1352 jcc@lydenoil.com

8151 Millis Road

3249 Wales Ave. NW Massillon, OH 44646local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com