



Lyden Oil Company

ProGuard

Product Information

ProGuard SparKut 185

ProGuard SparKut 185 is a dark colored , active sulfur and low odor cutting oil. The extreme pressure additives are effective in reducing friction at the chip tool interface. This allows for peak performance in ferrous metal applications.

Typical Properties

ProGuard SparKut 185

Color	Dark Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	0.9260
Density, lbs/gal	7.711
Viscosity, cSt @ 40 °C	38
Oil, wt. %	60.0
Sulfur, wt. %	6.0
Chlorine, wt. %	5.0
Lubricity additive, wt. %	10.0

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com