



Lyden Oil Company

ProGuard

Product Information

ProGuard SparKut HP

ProGuard SparKut HP is a sulfur-free petroleum oil based cutting lubricant. It is safe for use on all metals. **ProGuard SparKut HP** contains extreme pressure additives for extended tool life.

Typical Properties

ProGuard SparKut HP

Color	Golden Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	0.9159
Density, lbs/gal	7.629
Viscosity, cSt @ 40 °C	20-30
Chlorine	Present

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com