



Lyden Oil Company

ProGuard

Product Information

ProGuard SparSol 38NC

MACHINING AND GRINDING COOLANT

ProGuard SparSol 38NC is a premium grade, chlorine-free soluble machining and grinding coolant. This product is formulated for machining ferrous and non-ferrous alloys. **ProGuard SparSol 38NC** is a clean running bio-stable machining and grinding coolant that provides excellent tool life and surface finish.

Typical Applications

Milling
Grinding

Turning
Sawing

Refractometer Readings, brix

4.80 at 5%
9.50 at 10%

Typical Properties

ProGuard SparSol 38NC

Product Code Number	808116
Color	Gold-Amber
Odor	Characteristic
Appearance	Clear Liquid
Specific Gravity, ASTM D-1298	0.9432
Density, lbs/gal	7.854
Ph (diluted 10:1)	9.40-10.0
Pour Point, °F	10
Chlorine	Nil

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com