



Lyden Oil Company

ProGuard

Product Information

ProGuard TC 2-Cycle Oil—Land

ProGuard TC 2-Cycle Oil-Land is a high quality lubricant blended to meet the latest API and JASO requirements. It is recommended for superior performance in high temperature (air-cooled) engines due to its excellent thermal stability.

ProGuard TC 2-Cycle Oil-Land provides excellent cold-temperature properties, maintaining fluidity at extremely low temperatures. It contains additive chemistry that keeps the system clean and reduces the tendency to smoke through the use of synthetic polymeric thickeners and not heavy viscosity base oils.

Specifications:

Meets the requirements of:

API TA, TB, TC
JASO FB, FC, FD
ISO-L-EGB, ISO-LO-EGC, ISO-L-EGD
TISI (Thailand Industrial Standards Institute)
Approved for Chainsaw Use

Typical Properties

ProGuard

TC 2-Cycle Oil-Land

Viscosity, ASTM D-445	
cSt. at 100° C	7.9
cSt. at 40° C	58.0
Viscosity Index	101
Flash Point, ° C, ASTM D-92	252
Pour Point, ° C, ASTM D-97	-20
API Gravity, ASTM D-287	38.6

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarps Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com