



Lyden Oil Company

ProGuard

Product Information

ProGuard TriPurpose

ProGuard TriPurpose is a light colored and low odor multipurpose oil. The extreme pressure additives are effective in reducing friction at the chip tool interface. This allows for peak performance in ferrous and Non-Ferrous metal applications. This product has found applications in grinding, cutting, screw machines as well as general purpose machining.

Typical Properties

ProGuard TriPurpose

Product Code Number	07168-AB
Viscosity, ASTM D-445 SUS at 40 °C	190
cSt at 40 °C	32
Flash Point, °C (°F), ASTM D-92	196 (385)
API Gravity	25.0
Appearance	Yellow, Clear Liquid
Density, lbs/gal	7.33
Chlorine	Present

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarms Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com

