



# Lyden Oil Company

## PROGUARD

### Product Information

#### **PROGUARD XAW II Hydraulic Fluid**

**PROGUARD XAW II Hydraulic Fluids** are moderate duty, anti-wear hydraulic fluids formulated to meet high output, high pressure or high speed, vane and gear type hydraulic applications where elevated levels of anti-wear are needed while keeping your system trouble free and free of varnish build up.

**PROGUARD XAW II Hydraulic Fluids** are also recommended for rotary vane-type compressors, machine tools and circulating systems.

#### **Benefits:**

- Excellent Rust and Wear Protection
- Low Deposit Formation
- Good Demulsibility
- Low Air Entrainment
- Excellent Oxidation Resistance and Anti-Foaming Properties

**Meets the approval requirements of:** Denison HF-O, HF-1, HF-2, Vickers M-2950-S, I-286-S and Cincinnati Machine P-68 (ISO 32), P-69 (ISO 68) & P-70 (ISO 46), US Steel 127, 136, Racine Vane Pumps-Variable Volume.

#### **Typical Physical Characteristics:**

<b>PROGUARD XAW II</b>	<b>32</b>	<b>46</b>	<b>68</b>
ISO Viscosity Grade	32	46	68
Viscosity, ASTM D-445			
cSt. at 40° C	31	43	64
cSt. at 100° C	5.4	6.7	8.2
Viscosity Index	100	98	96
Flash Point, ASTM D-93, °F (°C)	350 (176)	350 (176)	350 (176)
Oxidation Life, ASTM D-943, hrs.	>5500	>5500	>5500
Rust Test, ASTM D-665	Pass	Pass	Pass
Pour Point, °F	-20	-20	-10

#### **Lyden Oil Company**

30692 Tracy Road  
Walbridge, OH 43465

1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarps Drive  
Youngstown, OH 44515

1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906

1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317

local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646

local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com